



Functional 3-layer fleece jacket

3-layer functional fabric with TPU membrane
 Wind- and water-proof (5,000 mm water column), breathable and permeable to vapour (2,000 g/m²/24h)
 Non-taped seams
 Full-length storm flap, elastic cord with stoppers on hem
 2 zipped concealed pockets
 JN1006: Breast pocket
 JN1007: Slightly waisted
 Middle layer: water-proof, breathable and wind-proof TPU membrane

Fabric:	Outer fabric (350 g/m ²): 100% polyester Lining: 100% polyester
Country of origin:	Volksrepublik China
Customs tariff number	61013090

Care instructions



Partner article



Ladies' Bonded Fleece Jacket
 Art-Nr.: JN1007

Available colours

	S	M	L	XL	XXL	3XL
Weight in g	706g	754g	766g	808g	826g	915g
VPE (pcs. per inner packaging / pcs. per outer packaging)	1/10	1/10	1/10	1/10	1/10	1/10
measurements in cm	S	M	L	XL	XXL	3XL
1/2 chest:	54,00 cm	57,00 cm	60,00 cm	63,00 cm	66,00 cm	69,00 cm
1/2 bottom width:	52,00 cm	55,00 cm	58,00 cm	61,00 cm	64,00 cm	67,00 cm
front length from shoulder:	71,00 cm	72,00 cm	73,00 cm	74,00 cm	76,00 cm	79,00 cm
length back from shoulder:	76,00 cm	77,00 cm	78,00 cm	79,00 cm	81,00 cm	84,00 cm
sleeve length incl. shoulder:	78,00 cm	80,00 cm	82,00 cm	84,00 cm	87,00 cm	90,00 cm

Available colours

 aqua/navy (7461C, 5395C)
 green/navy (583U, 5395C)
 red/carbon (201C, 447U)

 black/red (blackC, 201C)
 navy/red (296C, 201C)

 carbon/black (425C, blackC)
 orange/carbon (716U, 425C)



Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m² within 24 hours. The higher this figure, the more breathable the textile is.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.